

AQUAFORM-230

WATER-BASED CONCRETE FORM RELEASE AGENT

An environmentally friendly version of the company's heritage release agent, AQUAFORM-230 is comprised of neutralized vegetable oils in mineral oil that contains no waxes, silicones, or carcinogens; it's also solventless and non-toxic. Concepts of its art are established on last novel principles in production and developments of contemporary form Release Agents e.g. Green and most environment friendly composition to be made, provide long life and extensive reuse of frameworks, to remain hard, non-powdery, stain-free concrete surface with a minimum number of defects, permit clean release of formwork from the hardened concrete during stripping and Cost cuts in purchase and usage of them.

ADVANTAGES

- Low Volatile Organic Compound (V.O.C.) content.
- Equally effective on all types of forming materials and form liners including elastomeric, PVC, and EPS
- Allows for fast and easy stripping of formwork
- Highly stable during placement and vibration of concrete
- Does not stain or contaminate the finished concrete surface
- Suitable for high detail forms and architectural concrete finishes
- Increased corrosion resistance to steel surfaces
- Extends the life of forms and inhibits oxidation of metal forms
- Reduces labor cost of stripping and cleaning forms and equipment
- Compatible with both type of static and slip-forming

FIELD OF APPLICATION

AQUAFORM-230 in general is formulated to be used for all case of wooden, plastic and metallic forms, etc.

SUBSTRATE PREPARATION

All surfaces to be coated with AQUAFORM-230 must be clean and free from grease, dirt and old concrete.

COVERAGE

AQUAFORM-230 should be applied at the following stated coverage rates to obtain a thin and even film over the entire surface of the form or formwork:

- Timber Formwork ~ 1 L per 10 – 15 m²
- Metal Formwork ~ 1 L per 20 – 25 m²

APPLICATION

Surface Preparation: Forms must be clean and free of any dust, dirt, laitance, hardened concrete or residue that might discolor new concrete.



موسسه استاندارد و تحقیقات صنعتی ایران
تأییدیه صلاحیت آزمایشگاه همکار



مرکز ملی تأیید صلاحیت ایران
ISO / IEC 17025



مجوز صادرات
به اتحادیه اروپا



استاندارد ملی ایران

تهران، خیابان سهروردی شمالی، خیابان شهید قندی غربی، ساختمان شماره ۱۲۴، واحد ۱ | تلفکس: ۸۷۷۵۱۴

www.abadgarangroup.com

info@abadgarangroup.com



واحد تولیدی نمونه ملی

Application: Apply AQUAFORM-230 with a brush, roller, or pressurized sprayer. Wipe off excess and drips with a clean, soft rag. Wait a minimum of 60 minutes before pouring Concrete.

New Wood Forms: Apply initial coat of AQUAFORM-230 at a rate of above recommended and do not wipe. Allow release agent to absorb into wood surface. For extremely porous forms a second saturation coat may be necessary prior to first use. Allow forms to dry, then recoat and wipe excess as stated above.

Cleanup

Clean tools and equipment used to apply AQUAFORM-230 with detergent and warm water.

PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid
Color	White
Solubility in Water	Totally miscible
Specific gravity of fresh mortar	0.98±0.02 g/cm ³
Stability	No Case of differentiation in phases

STORAGE & SHELF LIFE

Shelf life: 1 year in the original package

Storage condition: should be protected from direct sunlight and moisture. Keep Gallons in the temperature range between +10°C and +30°C.

Higher temperatures could disrupt the stability of primary emulsion and would be needed to be premixed when using.

Packing: 20 lit Container

HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet (available on request) containing physical, ecological, toxicological and other safety-related data.

TECHNICAL SERVICE

The ABADGARAN INTERNATIONAL GROUP Technical Department is available to assist you in the correct use of our products and its resources are at your disposal entirely without obligation.

All data presented in this technical datasheet are based on our last researches in ABADGARAN CONSTRUCTION CHEMICALS laboratories and are just as a guide for choosing appropriate material. Therefore users should conduct a sufficient investigation to establish the suitability and conformity of any product for intended uses.



موسسه استاندارد و تحقیقات صنعتی ایران
تأییدیه صلاحیت آزمایشگاه همکار



مرکز ملی تأیید صلاحیت ایران
ISO / IEC 17025



مجوز صادرات
به اتحادیه اروپا



استاندارد ملی ایران



واحد تولیدی نمونه ملی

تهران، خیابان سهروردی شمالی، خیابان شهید قندی غربی، ساختمان شماره ۱۲۴، واحد ۱ | تلفکس: ۸۷۷۵۴

www.abadgarangroup.com

info@abadgarangroup.com