



POZZOCRETE WATER REDUCER / PLASTICIZER ADMIXTURE

POZZOCRETE is a water reducer and plasticizing admixture. It meets the requirements of the following standards: ASTM C494/C494 M TYPE A EN 934 **ISIRI 2930**

APPLICATION

- Suitable for producing pumpable concrete
- Enables production and transportation of concrete in normal weather conditions
- Ready mix concrete
- Slabs, foundations, columns, shear and retaining walls, deck bridges, etc.
- Design of concrete mixes with fully-crushed aggregates

ADVANTAGES

- Reduces water-cement ratio up to 12%
- Increases workability and workability retention of concrete
- Improves pumpability of concrete
- It can be used with all types of Portland cement
- Prevents creep and shrinkage of concrete
- Increases the compressive strength of concrete
- Prevents bleeding and segregation of concrete

DOSAGE

The optimum dosage of POZZOCRETE can be determined by trials in the site. Depending on concrete mix design (sizes and types of aggregates, cement content, water/cement ratio, ambient temperature and concreting conditions), a dosage of between 0.5 and 1.5 percent by weight of cement or cementitious material is recommended.

For use with other range of dosage, contact ABADGARAN GROUP Technical Services Department.

DIRECTION OF USE

- 1- POZZOCRETE could be added to a part of concrete mixing water then added to the concrete
- 2- POZZOCRETE could be added to the concrete mix during the mixing cycle at the same time as the water or the aggregate or it could be added to ready-mix concrete before placing concrete.
- 3- Admixtures must be weighed carefully.

PHYSICAL AND CHEMICAL PROPERTIES

Specific gravity: 1.08±0.05 g/cm³

Physical state: Liquid Color: Dark brown

Chloride Content: Nil to EN 934-2















Construction Chemicals Producers

Tunnelina Membership

Iran Standard's Mark Iran Standard's Mark ISO 9001:2008
Holders Association TÜV NORD Iran PJS

Center of Iran ISO / IEC 17025

Institute

Mine and Trade

Revision Date: 10/29/2014





STORAGE

Shelf life: 1 year in the original package

Storage condition: Should be protected from direct sunlight and frost. Keep container in the

temperature range between +10°C and +30°C.

Packing: 22 kg container or 1000 kg tank

HEALTH AND SAFETY

This product does not contain any substances hazardous to human health and the environment. However, it should not be swallowed and contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water. POZZOCRETE is not flammable. For further information refer to the material safety data sheet. MSDS is available at ABADGARAN GROUP website.

TECHNICAL SERVICE

The ABADGARAN GROUP Technical Department is available to assist you in the correct use of our products and its resources are at your disposal entirely without obligation.







Tunnelina

Membership



Iran Standard's Mark











Center of Iran ISO / IEC 17025

Institute

Revision Date: 10/29/2014